

B E S T I N C L A S S

HOMEXTM
INNOVATIVE EXTERIORS



Four SeasonsTM

Insulated Siding

For Every Reason. A Season For You.

What is it that you want in siding — beauty, energy savings, or sound reduction? Now, there's no need to choose. Four SeasonsTM, from HOMEX, gives you the look and feel of premium wood, and thermal foam backing for saving energy and reducing noise. Summer, winter, spring or fall, Four SeasonsTM is for you.

- Rich, deeply-etched wood-grain pattern
- Energy saving Four SeasonsTM FullbackTM foam insulation backing
- Reduces outside noise for quiet comfort
- Four SeasonsTM dent resistant panels provide superior strength
- Extra strong and rigid to withstand extreme winds
- Retains original shape year after year
- This HOMEXTM product is covered by a Limited Lifetime Warranty



FULLBACKTM
THERMAL SUPPORT SYSTEM





Four Seasons™

Insulated Siding

B E S T I N C L A S S

Colors/Color Numbers



White Birch 02



Warm Sandalwood 17



Sunny Maize 22



Summer Wheat 26



Harbor Stone 44



Vintage Sage* 55



Adobe Clay* 60



Wicker Beige* 65

*Premium colors made with Armor Coat UVA™ and Solarkote®PB.



Produced with Armor Coat UVA™ and Solarkote®PB Acrylic High-Performance Polymers

An exclusive blend of the best raw materials, UV stabilizers and performance modifiers offer superb color retention and weatherability.



Enhanced Impact Resistance

Unlike conventional siding that can only withstand minimal impacts of 60 to 90 psi, Four Seasons dent resistant panels can handle impacts of up to 300 psi.



Insect Resistant Treated Foam

Four Seasons panels feature Fullback's patented Perform Guard to create an impregnable defense against termites. Treated foam panels are shown above at right versus untreated panels shown at left.

Color representations shown may vary slightly from actual product color.

Profiles Available

Double 4, Double 6, and Dutch Lap 4.5

Product Test Data

HOMEX Vinyl Siding passes or exceeds all industry standards per ASTM D3679.

Siding Thickness: D6.....	0.048" ± .001"
D4, DL4.5.....	0.044" ± .001"
Specific Gravity.....	1.45
Tensile Strength (PSI).....	7,154
Tensile Modulus (PSI).....	416,900
IZOD Impact Strength @ 32° F.....	Passes per ASTM D3679
Heat Deflection Temp. @ 264 PSI.....	169° F
Coefficient of Linear Expansion.....	3.30 x 10 ⁻⁵
Weight: D6.....	70 lbs. per square
D4, DL4.5.....	52 lbs. per square
Warpage.....	0.00"
Heat Shrinkage.....	0.3%
Impact Resistant.....	Passes per ASTM D3679
Surface Distortion @ 140° F.....	0
Fire Rating.....	Class A
Flame Spread index.....	10
Smoke Developed.....	395
Fuel Contribution.....	0
Average Time of Burning.....	Self Extinguishing
Average Extent of Burning.....	2.379mm
Weathering.....	Passes per ASTM D3679
Windload Rating*.....	193 MPH


*(Wind velocity based on IBC).



Four Seasons is available in the rich, deep-etched woodgrain of our Traditional (top) and Dutchlap profiles.



Style Crest, Inc.
2450 Enterprise St.
Fremont, Ohio 43420
800.925.4440
www.homexsiding.com

Solarkote® is a registered trademark of Arkema, Inc.
 Made in U.S.A. by America's dedicated workforce.
Specifications subject to change without notice.

