

T H E G O O D L I F E

HOMEX
INNOVATIVE EXTERIORS

WEDGEWOOD

SQUARE™

Enduring Beauty.

Lasting style. Impact resistant. Textured wood-grain look. WedgeWood Square™ comes in two profiles of warm and inviting colors, made with high performance polymers for lasting beauty.

- Large palette of beautiful colors
- Weather resistant; Impact resistant
- Positive locking system assures easier installation
- This HOMEX™ product is covered by a Limited Lifetime Warranty



WEDGEWOOD

SQUARE™

T H E G O O D L I F E

Colors/Color Numbers



White Birch 02



Classic Sand 11



New Linen 13†



Warm Sandalwood 17



Sunny Maize 22



Summer Wheat 26



Autumn Taupe 28†



Harbor Stone 44



Vintage Sage* 55†



Wicker Beige* 65†



Victorian Slate* 67



Terra Clay* 69



Charcoal Grey* 84†

*Premium colors made with Armor Coat UVA™.

† Colors available in Dutch Lap 4.5 only.

Profiles Available

Double 4.5 and Dutch Lap 4.5

Product Test Data

HOMEX™ Vinyl Siding passes or exceeds all industry standards per ASTM D3679.

Siding Thickness	0.040" ± .001"
Specific Gravity	1.45
Tensile Strength (PSI)	7,000
Tensile Modulus (PSI)	400,000
IZOD Impact Strength @ 32° F	Passes per ASTM D3679
Heat Deflection Temp. @ 264 PSI	163° F
Coefficient of Linear Expansion	2.69 x 10 ⁻⁵
Warpage	0.00"
Heat Shrinkage	0.3%
Impact Resistant	Passes per ASTM D3679
Surface Distortion @ 140° F	0
Fire Rating	Class A
Flame Spread index	20
Smoke Developed	275
Fuel Contribution	0
Average Time of Burning	Self Extinguishing
Average Extent of Burning	2.379mm
Weathering	Passes per ASTM D3679
Windload Rating*	162 MPH

*(Wind velocity based on IBC).

Color representations shown may vary slightly from actual product color.



Style Crest, Inc.
2450 Enterprise St.
Fremont, Ohio 43420
800.846.9599
www.homexsiding.com

Made in U.S.A. by America's dedicated workforce.
Specifications subject to change without notice.

